



## **SPEEDWAY REGULATION UPDATES 2|5|24**

### **UPDATED METHANOL CHECK PROCEDURE:**

Tech officials will mix racers methanol and distilled water. To pass, the mixture must be clear. If the sample becomes cloudy, it is a DQ.

It is recommended to get your methanol checked before you race it.

### **UPDATED GAS CHECK PROCEDURE:**

Tech officials will source fuel for control sample. The fuel probe will be placed in the control sample and zeroed. Racer's fuel will then be tested and must check like tech's sample or it is a DQ. Racer's fuel must be in tech's tolerance or it is a DQ.

It is recommended to get your gas checked before you race it.

### **ORIGINAL**

**40.4.6.2:** Mini pipe must be round .750" OD steel tubing & constant diameter for entire length of pipe. (No multi stage)

### **NEW (WILL TAKE AFFECT 3|31|24)**

**40.4.6.2:** Mini pipe must be round .750" OD steel tubing & constant diameter for entire length of pipe. (No multi stage). Must have the long nipple on the pipe. The muffler must be screwed all the way into the nipple of the header. There may be no excessive amount of threads showing outside of the nipple. The muffler must be tight when checked. The muffler can be checked with the clamps on or off. No loose mufflers. Muffler threads can be compared to another stock muffler. Threads must be **STOCK**.